



**Specifications Ledvance LED Downlight Performance DN155 Zigbee White 14W 1600lm - 840 Cool White | 180mm - Cutout 155mm**

[View Product](#)

## General Information

|                          |   |
|--------------------------|---|
| SKU                      | 243656                                  |
| EAN                      | 4058075459892                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | DL UGR19 DN155 PFM 14W/840 ZBVR WT LEDV |
| Any Lamp all-in warranty | 3 Years                                 |
| Average Lifetime (h)     | 70000                                   |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Wireless connection         | Zigbee            |
| Lighting Control            | Zigbee            |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                                |
|--------------------------|--------------------------------|
| Including bulb           | Yes                            |
| Beam Angle (degree)      | 65                             |
| Luminous Efficacy (lm/W) | 114                            |
| Power factor             | >0.90                          |
| Installation Depth (mm)  | 100                            |
| Unified Glare Rating     | < 19 - for offices and schools |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 155               |
| IP-rating              | IP54              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +45        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | DN155             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 65  |
| Diameter (mm) | 180 |

## Why Any-lamp?

## Sensor Information

 Order from the **largest lighting specialist** in Europe  **Customised** quotation  
 Type of sensor  No Sensor

 Up to **7 years warranty**  **Easy** return process